

X1

35 to 47 Engine HP

McCORMICK



Tractor Model		X1.35	X1.45	X1.45C
Rated Engine	<i>HP (kW)</i>	35 (26)	47 (35)	47 (35)
Rated Engine Speed		2800 RPM		
Rated PTO	<i>HP (kW)</i>	29 (21)	42 (31)	42 (31)
Engine Type		3-cylinder diesel	4-cylinder diesel	
Displacement		1.7 L	2.3 L	
Aspiration		Natural, with dual element air cleaner		
Emissions System		EPA Tier 4, using combined DOC + DPF		
Fuel Capacity	<i>gal (liters)</i>	9.3 (35)		
Main Clutch		Dry single disc, operated via left side foot pedal		
Speeds		12 forward x 12 reverse (4 gears, 3 ranges)		
Shuttle Type		Synchronized, with left hand shuttle lever		
Differential Lock		Mechanical, heel pedal		
Rear Brakes		Wet disc brakes with suspended R and L pedals		
Front Axle Type		4wd with mechanical engagement		
Rear PTO Type		Independent, electronically engaged		
Rear PTO Speed		540 and 540e rpm standard		
Implement Hydraulics		Open center system		
Hyd. Flow at Remotes	<i>gpm (lpm)</i>	8.9 (34)	11.1 (42)	
Loader Joystick		Standard with 2 mid mount valves		
Rear Remote Valves		0 standard, 2 optional	2 standard	
3-point Type		Category I with telescopic stabilizers and lower links		
3-point Lift Capacity	<i>lb (kg)</i>	3,306 lbs at ball ends		
Operator's Area		Folding ROPS	Cab w/HVAC	
Seat and Steering		Adjustable vinyl seat; tilt steering		
Overall Length	<i>in (mm)</i>	130 (3300)		
Wheelbase	<i>in (mm)</i>	70.9 (1800)		
Height over ROPS/Cab	<i>in (mm)</i>	94 (2390)	96 (2440)	97 (2460)
Base Weight	<i>lb (kg)</i>	4,053 (8935)	4,118 (9080)	4,442 (9790)

Loader Model		160C	180C
Max. Lift Height	<i>in (mm)</i>	92.5 (2350)	101 (2565)
Under Bucket			
Lift Capacity to Max. Height	<i>lb (kg)</i>	2,361	2,628
19.5" Forward of Pivot			
Breakout Force	<i>lb (kg)</i>	2,985	3,711
19.5" Forward of Pivot			
Rollback Force	<i>lb (kg)</i>	4,098	5,721
31.5" Forward of Pivot			
Compatible Tractor Models		X1.35	X1.45 X1.45C

